

AMENDMENTS TO THE CLAIMS:

The following listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims:

Claims 1-22 (canceled).

Claim 23 (currently amended): A method of packaging leaky fuel rods for transport and subsequent storage of at least 50 years, each leaky fuel rod containing pellets of fuel material in tubular cladding and being closed at ends of the tubular cladding and presenting a sealing defect, each leaky fuel rod coming from at least one fuel assembly and being deposited in a first step underwater in a pool, the method comprising:

- making available a plurality of capsules, each of the plurality of capsules for receiving one of the leaky fuel rods, and each of the plurality of capsules including a tubular sheath and two end plugs, at least one of the two end plugs being removable, each of the plurality of capsules having a longitudinal axis;

- placing a loading structure in the pool, the loading structure having a plurality of locations, each location being capable of receiving one of the plurality of capsules so that the longitudinal axes of the plurality of capsules are in a vertical orientation, the loading structure having an open top end;

- securing, on the open top end, a device for loading one of the leaky fuel rods into the at least one capsule, the device for loading having an opening and a guide device capable of being placed at the opening;

- inserting the leaky fuel rods in the pool one by one into empty ones of the plurality of capsules in the loading structure at ~~a at least one~~ loading location of the plurality of locations, the inserting for each leaky fuel rod including: unscrewing one of the end plugs of a respective capsule of the plurality of capsules, the end plug being situated at a capsule top end; placing the leaky fuel rod into the respective capsule via the guide device; and screwing the one end plug at the top end of the capsule back into place;

moving each capsule containing the leaky fuel rod from the ~~at least one~~ loading location to another location of the plurality of locations of the loading structure different from the ~~at least one~~ loading location; and

transporting and storing the capsules containing the leaky fuel rods.

Claim 24 (previously presented): The method according to claim 23, wherein the loading structure comprises a handling top nozzle and a bottom nozzle both extending transversely, the nozzles being assembled to each other by longitudinally-extending tie-bars, together with a plurality of transversely-extending spacer plates distributed in the longitudinal direction of the loading structure and each comprising an array of openings, the array of openings including first openings serving to pass and hold a respective capsule, the array of openings also including second openings having engaged therein the tie-bars, the loading structure including a first location for loading capsules in a vicinity of a corner of a square-shaped cross-section of the loading structure.

Claim 25 (previously presented): The method according to claim 24, wherein the loading structure further comprises a second location in which the bottom nozzle of the loading structure includes an opening for receiving a closure plug at the bottom end of the respective capsule, the location having placed therein a peg projecting into the loading structure, wherein the bottom plugs and top plugs of the capsules are pierced axially by respective channels having respective channel-closure valves located therein and urged towards a closed position by respective helical springs, an open end of the channel in the top plug including an arrangement for connection to a duct for feeding inert gas, and wherein after a leaky fuel rod has been inserted in a capsule and the top plug has been screwed back onto the capsule in the loading structure first location, the capsule is transferred to the second location for filling with inert gas, the bottom plug of the capsule is inserted into the corresponding housing of the bottom nozzle, so that the projecting peg lifts the valve of the bottom plug into an open position, and an inert gas under pressure is delivered into the inlet end portion of the channel in the top plug, so as to open the valve of the top plug and then fill the inside space of the capsule with inert gas, the water and the gas contained in the capsule being expelled through the channel in the bottom plug, the delivery of inert gas being stopped after the inside space of the capsule has been filled, so that the closure

valve of the top plug recloses, with the leaky fuel rod then being stored inside the capsule in an atmosphere of inert gas under pressure.

Claims 26 to 29 (canceled).

Claim 30 (previously presented): The method according to claim 23, wherein the leaky fuel rods coming from the at least one fuel assembly are placed in an intermediate storage arrangement before the inserting step.

Claim 31 (previously presented): The method according to claim 23, wherein the loading structure has the shape and the dimensions of one of the at least one fuel assemblies.

Claim 32 (previously presented): A method of packaging leaky fuel rods for transport and subsequent storage of at least 50 years, each leaky fuel rod containing pellets of fuel material in tubular cladding and being closed at ends of the tubular cladding and presenting a sealing defect, each leaky fuel rod coming from at least one fuel assembly and being deposited in a first step underwater in a pool, the method comprising:

- making available a plurality of capsules, each of the plurality of capsules for receiving one of the leaky fuel rods, and each of the plurality of capsules including a tubular sheath and two end plugs, at least one of the two end plugs being removable, each of the plurality of capsules having a longitudinal axis;

- placing a loading structure in the pool, the loading structure having a plurality of locations, each location being capable of receiving one of the plurality of capsules so that the longitudinal axes of the plurality of capsules are in a vertical orientation, the loading structure having an open top end;

- securing, on the open top end, a device for loading one of the leaky fuel rods into the at least one capsule, the device for loading having an opening and a guide device capable of being placed at the opening;

- inserting the leaky fuel rods in the pool one by one into empty ones of the plurality of capsules in the loading structure, the inserting for each leaky fuel rod including: unscrewing one of the end plugs of a respective capsule of the plurality of capsules, the end plug being situated at

a capsule top end; placing the leaky fuel rod into the respective capsule via the guide device; and screwing the one end plug at the top end of the capsule back into place;

placing each capsule containing the leaky fuel rod in one of the locations of the loading structure; and

transporting and storing the leaky fuel rods inside the capsules placed in the loading structure.

Claims 33 (previously presented): A method of packaging leaky fuel rods for transport and subsequent storage of at least 50 years, comprising:

depositing the leaky fuel rods in a pool;

making available a plurality of capsules, each of the plurality of capsules for receiving one of the leaky fuel rods, and each of the plurality of capsules including a tubular sheath and two end plugs, at least one of the two end plugs being removable, each of the plurality of capsules having a longitudinal axis;

placing a loading structure in the pool, the loading structure having a plurality of locations, each location being capable of receiving one of the plurality of capsules so that the longitudinal axes of the plurality of capsules are in a vertical orientation, the loading structure having an open top end;

securing, on the open top end, a device for loading one of the leaky fuel rods into the at least one capsule, the device for loading having an opening and a guide device capable of being placed at the opening;

inserting the leaky fuel rods in the pool one by one into empty ones of the plurality of capsules in the loading structure at a loading location of the plurality of locations, the inserting for each leaky fuel rod including: unscrewing one of the end plugs of a respective capsule of the plurality of capsules, the end plug being situated at a capsule top end; placing the leaky fuel rod into the respective capsule via the guide device; and screwing the one end plug at the top end of the capsule back into place;

moving each capsule containing the leaky fuel rod from the loading location to a different storage location of the plurality of locations; and

transporting and storing the leaky fuel rods inside the capsules while in the storage location.

Claim 34 (currently amended): The method as recited in claim 23 further comprising moving each of the capsules from the ~~at least one~~ loading location to a gas filling location of the plurality of locations, and filling an inside space of the capsule with an inert gas at the gas filling location.